SpillPro[®]






Simplex boom is an industry standard oil containment boom. Its' lightweight and reliable construction makes it ideal for shoreline and protected coastal protection. Simplex is an inexpensive boom, yet it features a high buoyancy reserve provided by stable closed cell foam log floats.

As an option a top cable can be added to increase the tensile strength of the boom for fast current and towing applications. Manufactured in fully welded 22oz PVC material, this boom is fitted with handles and anchor points, as well as being offered with a variety of accessories.

Simplex boom conforms to OPA90 requirements*. The boom is supplied with ASTM compliant interchangeable end connectors for rapid coupling of sections. End connectors are fitted with Zinc anodes.

*Simplex complies with United States Code of Federal Regulation (CFR) 33.Pt 154. App.C for Rivers and Canals, Inland and Great Lakes.

Standard Simplex boom conforms with ASTM standard F1523 f or Calm Water, Calm Water-Current and Protected Water







Specifications

Height:	12" / 300mm	18" / 460mm**	20" / 500mm	24"/610mm
Freeboard:	6" / 150mm	6" / 150mm	8" / 200mm	10" / 250mm
Draft:	6" / 150mm	12" / 300mm	12" / 300mm	14" / 360mm
Weight:	1.68 lbs/ft 2.49 kg/m	1.7 lbs/ft 2.5 kg/m	1.8 lbs/ft 2.67 kg/m	2.2 lbs/ft 3.27 kg/m
Top Tension:	Optional			
Bottom Tension:	1/4" / 6mm Galvanized Steel Chain			
Actual Tensile Strength:	5,000 lbs / 2,273 kg			
Section Lengths:	25, 50, 100ft / 7.5, 15, 30m			
Standard Connector:	ASTM Universal Slide*			
Anchoring Points:	At every section connector			
Fabric:	22 oz / 735 gsm PVC (other available on request)			
Colour:	High Visibility Yellow or Orange			
Anodes:	Fitted at section connectors			
Handles	Fitted along the boom			

^{*} Other connectors available on request

Optional Accessories: Anchor sets, Tidal Slides, Strong-Backs, Two Bridle, Marker Lights, Stand-Off Units, Alternative Connectors, Radar Reflective Material.

^{**} Standard model. Note: boom with less than 18" height will only comply with CFR33 for River/Canal.



Delivering Certainty

We're more than equipment suppliers. We're problem solvers.

And that's unique in the Australian market.

We can provide complete solutions for spills, workshop services and products as well as workplace safety and hygiene.

Everything you need. One point of contact

www.spillpro.com.au

OUR LOCATIONS —

SYDNEY	NEWCASTLE	MELBOURNE	BRISBANE
38 Ricketty St	4 Channel Rd	40 Latitude Blvd	20/388 Newman Rd
Mascot	Mayfield West	Thomastown	Geebung
NSW 2020	NSW 2304	VIC 3074	QLD 4034
P: 02 8999 8491	P: 02 4957 2886	P: 03 9999 9277	P: 07 3177 3096

PERTH	ADELAIDE	DARWIN
67 Howe St	8 Greenhill Rd	Level 16, 19 Smith St
Osborne Park	Wayville	Darwin
WA 6017	SA 5034	NT 0800
P: 08 6555 4083	P· 08 7070 1768	P· 08 7999 7822